



Technical Specifications

MARK/CUT SLICE® 135-P/HS Model 2

Model 135-P/HS for hot stamp marking & cutting tubing

Print location tolerance: ± 1 mm (0.04")

System resolution: ± 0.50 mm (.02")

Processes material at up to 15 inches per second

Will cut and mark up to 3,600 4" pieces of product per hour or 2,400 10" pieces per hour

Hot Stamp Technology system's printing time is variable; actual pieces per hour may vary.

Print Area: 3.0" (76 mm) wide X 3.0" (76mm) long

Center print, leading or trailing edge printing
Multiple prints without cutting
High, repeatable accuracy
Vertical and horizontal adjustments
Digital electronic controls with stepper motor ribbon advance
Meets Mil Spec MIL-M-81531(AS)
Compatible with Kingsley type holders

Capabilities: Handles printing and cutting of heat shrink and other soft tubing, including reeled adhesive-lined heat shrink. It also cuts up to 60 conductor flat ribbon cable with precision.

99 batch programs in memory
30 batch file programs, each one consisting of up to 10 standard programs
Remembers place in batch program if power is lost.

Blade: Guillotine-type custom-designed blade and die set made of hardened tool steel,
58-60 Rockwell C

Air Supply, Hot Stamp and Slice 135:	90psi/6bar, clean and dry
Power requirements:	115/230 Volts 50/60 cycles
Environmental:	10 - 35° C
Hot Stamp Temperature:	150 to 400° F

Overall Physical Dimensions:
Length = 43 in. (excluding reel) Width = 21.5 in. Height = 33.5 in. Weight = 100 lb.

FCC Class B Certification

Patents Pending **SLICE®** is a registered trademark of AMTI. All rights reserved.

AMTI
Division of Maxant

7540 Caldwell Ave. Niles, IL 60714
Tel. 847-588-2280 Fax 847-588-1920

slice@amti-products.com
www.amti-products.com